


Moisture-proof diffuser luminaire

LED Moisture-proof diffuser luminaire with IP66 protection rating and drip-edge effect for minimizing dirt and collection of dust for maximum hygienic requirements. Luminaire input power: 36.1 W, with dimmable constant current LED driver, especially suitable for industrial applications in adverse surroundings such as cold store halls and factories with increased ambient temperatures; patented InvisiClick for clipless mounting and opening of the cover. Cover and basic diffuser made of impact-resistant polycarbonate, temperature- and UV-resistant, made as a single injection-molded piece. LED service life lasts 100000 h before luminous flux is reduced to 95% of the initial value. Chromaticity tolerance (initial MacAdam): 3. Luminaire luminous flux: 6360 lm, Luminaire efficacy: 176 lm/W. Colour rendering $R_a > 80$, colour temperature 4000 K. Luminaire with symmetric narrow light distribution (narrow beam). Mounting via V2A standard spring clips to ceilings, walls or trunking. 5-pole connector terminal. ambient temperature: -40°C to $+44^{\circ}\text{C}$. Approved for indoor use with vertical or horizontal wall mounting (see installation instructions). Note: please contact your consultant if you are planning to use the luminaire in environments with chemical pollutants, high or condensing humidity and major variations in temperature. Complies with International Food Standard specifications. Designed for BESA box. Permissible for use in environments where the deposition of conductive dust on the luminaire can be expected (EN 60598-2-24). Protection class: SC1, 850 °C glow-wire tested. Luminaire wired with halogen-free leads, silicone-free, Impact strength: IK08, Dimensions: 1600 x 92 x 90 mm; weight: 3.41 kg.




ZS_AMP_F_AMPHIBIA_NB.jpg



ZS_AMP_M_Amphibia.wmf

Light Distribution

STD - standard



D45911_AMP_L_LT_6400-840_PC_NB_IVG.idt

- Light Source: LED
- Luminaire luminous flux*: 6360 lm
- Luminaire efficacy*: 176 lm/W
- Colour Rendering Index min.: 80
- Ballast: 1 x 28004034 LCI 75/125-550/300 o4a NF h28 EXC4
- Correlated colour temperature*: 4000 Kelvin
- Chromaticity tolerance (initial MacAdam): 3
- Rated median useful life*: L95 100000 h at 44 °C
- Luminaire input power*: 36.1 W Power factor = 0.95
- Standby Power*: 0.2 W
- Dimming: Dali dimmable to 1%
- Maintenance category CIE 97: E - Dust-proof IP5X
- Total harmonic distortion (THD): 10.30 %

This product contains a light source of energy efficiency class C.
Please also consult the additional information on the next page

AMPHIBIA PC



ZUMTOBEL

AMP L LT 6400-840 PC NB IVG

42929118

Moisture-proof diffuser luminaire

All values marked with an * are rated values. Connected electrical load and luminous flux are subject to an initial tolerance of +/- 10%, the most similar colour temperature is subject to an initial tolerance of +/- 150K. Unless stated otherwise, the values apply to an ambient temperature of 25°C. The level of luminous flux reduces over the life cycle due to technological reasons. The failure of up to 4 LED points causes no functional impairment and is therefore no reason for complaint.

We reserve the right to make technical changes without prior notice. 25.06.2025 © Zumtobel - 5-year guarantee in compliance with the terms of guarantee at www.zumtobel.com/guarantee