

96638021 TONIC M 3600-930 3GU SP BK




Tonic

LED spotlight for 3 phase track installations with spot light distribution and stabilized color temperature. Electronic, fixed output control gear. Class II electrical, IP20. Body: Die-cast aluminium black micro-textured paint. Reflector: PC sputtered. Spotlight rotatable through 360° and pivotable through 90°. Complete with 3000K LED


Dimensions: Ø85 x 150 mm
 Luminaire input power: 31.3 W
 Luminaire luminous flux: 3681 lm
 Luminaire efficacy: 118 lm/W
 Weight: 0.81 kg



TLG_TNC2_F_M_BK.jpg



TLG_TNC2_M_M.wmf



96638021_TONIC_M_3600_930_3GU_SP_BK.ltd

Lamp position: STD - standard
 Light Source: LED
 Luminaire luminous flux*: 3681 lm
 Luminaire efficacy*: 118 lm/W
 Colour Rendering Index min.: 90
 Correlated colour temperature*: 3000 Kelvin
 LOR: 1,00 ULOR: 0,00 DLOR: 1,00

Chromaticity tolerance (initial MacAdam): 3
 Rated median useful life*:
 L80 50000 h at 25 °C
 Ballast: 1x HF_
 Luminaire input power*: 31.3 W Power factor = 0.9
 Dimming: Fixed output
 Maintenance category CIE 97: D - Enclosed IP2X