

96638017 TONIC S 2800-940 3GU FL BK

LED 24W TON_2800_4K_FL	CB	UK CA	BEG	05	IP 20		CE							
------------------------	----	----------	-----	----	-------	--	----	--	--	--	--	--	--	--


Tonic

LED spotlight for 3 phase track installations with flood light distribution and stabilized color temperature. Electronic, fixed output control gear. Class II electrical, IP20. Body: Die-cast aluminium black micro-textured paint. Reflector: PC sputtered. Spotlight rotatable through 360° and pivotable through 90°. Complete with 4000K LED


Dimensions: Ø68 x 140 mm
 Luminaire input power: 24.5 W
 Luminaire luminous flux: 2935 lm
 Luminaire efficacy: 120 lm/W
 Weight: 0.52 kg



TLG_TNC2_F_S_BK.jpg



TLG_TNC2_M_S.wmf



96638017_TONIC_S_2800_940_3GU_FL_BK.idt

Lamp position: STD - standard
 Light Source: LED
 Luminaire luminous flux*: 2935 lm
 Luminaire efficacy*: 120 lm/W
 Colour Rendering Index min.: 90
 Correlated colour temperature*: 4000 Kelvin
 LOR: 1,00 ULOR: 0,00 DLOR: 1,00

Chromaticity tolerance (initial MacAdam): 3
 Rated median useful life*:
 L80 50000 h at 25 °C
 Ballast: 1x HF_
 Luminaire input power*: 24.5 W Power factor = 0.9
 Dimming: Fixed output
 Maintenance category CIE 97: D - Enclosed IP2X