



GLOBAL Trac adapters

The GA 100 MULTI Adapter™, designed by Nordic Aluminium, represents the latest innovation in adapter technology. There are no delays in the phase selector switch in the transition from one phase to another. The phase selector switch at the side of the adapter makes the use comfortable. Because both ends of the adapter are fitted with a locking mechanism, it can be removed directly from the track without turning it.



Adapter for all lighting tracks

MULTI Adapters are also designed to work with other manufacturers' lighting tracks. This means that the light manufacturer or fitter does not have to worry about the track on which the light will be mounted. Nordic Aluminium's three-circuit adapters include a wide selection of MULTI Adapters. The adapters come in three standard colours: grey, white and black. Adapters include several patented solutions. The materials used are halogen free and flame resistant.



Most popular adapter in the world

Our GA 69 MULTI Adapter is the world's most sold adapter. Its quality and reliability are unequalled. Product testing and 100% quality assurance are an integral part of Nordic Aluminium's strategy.



For all power supply needs


Continuous product development is essential for Nordic Aluminium. New products include a Schuko adapter. With this product the lighting track can be used for other power supply needs than lighting. It is a useful solution for meeting electricity needs in stores and small industrial premises.



3-circuit adapters

Available colours: -1 grey (RAL 7040), -2 black (RAL 9005), -3 white (RAL 9010).

GA 100



GA 100 circuit-selector adapter

Type	EAN code	Colour	PCS/ Package
GA 100-1	64100 14 530 00-6	Grey	10/100
GA 100-2	64100 14 531 00-3	Black	10/100
GA 100-3	64100 14 532 00-0	White	10/100

Truly modular adapter: end cover can be changed to allow for GAC version or trafo box installations.

MULTI Adapter™

- 10 A, 250 V, Safety class I
- Max. pull strength 100 N
- Max. torque 2.5 Nm
- To be used with stranded wire 0.5 ... 1 mm²

Slot connection. The conductors are pressed into the connectors by the cable mounting tool GB 66CT.

Type

EAN code

Colour

PCS/
Package

GA 100L-1

GA 100L-2

GA 100L-3

MULTI Adapter

MULTI Adapter

MULTI Adapter

Grey

Black

White

100/3200

100/3200

100/3200

Optional cable grip

Slot connection tool

100/5000

1/50

Grey

Black

White

5/50

5/50

5/50

Grey

Black

White

5/50

5/50

5/50

Grey

Black

White

5/50

5/50

5/50

Grey

Black

White

5/50

5/50

5/50

Grey

Black

White

5/50

5/50

5/50

Grey

Black

White

5/50

5/50

5/50

Grey

Black

White

5/50

5/50

5/50

Grey

Black

White

5/50

5/50

5/50

Grey

Black

White

5/50

5/50

5/50

Grey

Black

White

5/50

5/50

5/50

Grey

Black

White

5/50

5/50

5/50

Grey

Black

White

5/50

5/50

5/50

Grey

Black

White

5/50

5/50

5/50

Grey

Black

White

5/50

5/50

5/50

Grey

Black

White

5/50

5/50

5/50

Grey

Black

White

5/50

5/50

5/50

Grey

Black

White

5/50

5/50

5/50

Grey

Black

White

5/50

5/50

5/50

Grey

Black

White

5/50

5/50

5/50

Grey

Black

White

5/50

5/50

5/50

Grey

Black

White

5/50

5/50

5/50

Grey

Black

White

5/50

5/50

5/50

Grey

Black

White

5/50

5/50

5/50

Grey

Black

White

5/50

5/50

5/50

Grey

Black

White

5/50

5/50

5/50

Grey

Black

White

5/50

5/50

5/50

Grey

Black

White

5/50

5/50

5/50

Grey

Black

White

5/50

5/50

5/50

Grey

Black

White

5/50

5/50

5/50

Grey

Black

White

5/50

5/50

5/50

Grey

Black

White

5/50

5/50

5/50

Grey

Black

White

5/50

5/50

5/50

Grey

Black

White

5/50

5/50

5/50

Grey

Black

White

5/50

5/50

5/50

Grey

Black

White

5/50

5/50

5/50

Grey

Black

White

5/50

5/50

5/50

Grey

Black

White

5/50

5/50

5/50

Grey

Black

White

5/50

5/50

5/50

Grey

Black

White

5/50

5/50

5/50

Grey

Black

White

5/50

5/50

5/50

Grey

Black

White

5/50

5/50

5/50

Grey

Black

White

5/50

5/50

5/50

Grey

Black

White

5/50

5/50

5/50

Grey

Black

White

5/50

5/50

5/50

Grey

Black

White

5/50

5/50


5/50

Grey


Black

3-circuit adapters


Available colours: -1 grey (RAL 7040), -2 black (RAL 9005), -3 white (RAL 9010).




GA 300 circuit selector adapter. Phase 2 preselected.			
Type	EAN code	Colour	PCS/ Package
GA300-1	64100 14 530 43-3	Grey	10/100
GA300-2	64100 14 530 44-0	Black	10/100
GA300-3	64100 14 530 45-7	White	10/100
GA300L-1	64100 14 530 46-4	Grey	100/4800
GA300L-2	64100 14 530 47-1	Black	100/4800
GA300L-3	64100 14 530 48-8	White	100/4800
- A discreet adapter for elegant housing solutions - For GLOBAL Trac Pro XTS and XTSF tracs - 3 A, 250 V, Safety class I - Max pull strength 50 N - Max torque 2.5 Nm - To be used with stranded wire - Cable Grip CG 100			
Slot Connection. The conductors are pressed into the connectors by the Slot Plug (included) using for example a Torx 10 screwdriver.			



GA 300PP adapter, plastic parts.		
Type	Colour	PCS/ Package
GA300PP-1	Grey	100
GA300PP-2	Black	100
GA300PP-3	White	100
- For customized solutions - No metal connectors - For mechanical support only		



GA 300B Adapter body		
Type	Colour	PCS/ Package
GA300B-1	Grey	100
GA300B-2	Black	100
GA300B-3	White	100
- For customized solutions		




GA 300NB Adapter body		
Type	Colour	PCS/ Package
GA300NB-1	Grey	100
GA300NB-2	Black	100
GA300NB-3	White	100
- For class II customized solutions - No ground connector - Without locking lever		

3-circuit adapters

Available colours: -1 grey (RAL 7040), -2 black (RAL 9005), -3 white (RAL 9010).

XTSA 68




CG 75




Type	EAN code	Colour	PCS/ Package
XTSA 68-1	64100 14 530 73-0	Grey	10/100
XTSA 68-2	64100 14 520 68-7	Black	10/100
XTSA 68-3	64100 14 530 68-6	White	10/100
XTSA 68L-1		Grey	100/3200
XTSA 68L-2		Black	100/3200
XTSA 68L-3		White	100/3200
CG 75	64100 14 530 77-8	Optional cable grip	100/5000
MULTI Adapter™			
- 10 A, 250 V, Safety class I			
- Max. pull strength 100 N			
- Max. torque 2.5 Nm			
- Connecting conductors max. 3 x 1.5 mm ²			
Screw-in connection. The conductors are connected with screws.			

XTSA 67



XTSA 67S



Type	EAN code	Colour	PCS/ Package
XTSA 67-1	64100 14 500 46-7	Grey	10/100
XTSA 67-2	64100 14 520 67-0	Black	10/100
XTSA 67-3	64100 14 530 67-9	White	10/100
XTSA 67S-3	64100 14 500 44-3	Black	5/50
XTSA 67S-3	64100 14 531 67-6	White	5/50
- For GLOBAL Trac Pro tracks XTS and XTSF traces			
- 16 A, 250 V/400 V, Safety class I			
- Max. pull strength 100 N			
- Max. torque 2.5 Nm			
- Connecting conductors max. 5 x 2.5 mm ²			


Nipples for 3-circuit adapters

Available colours: -1 grey (RAL 7040), -2 black (RAL 9005), -3 white (RAL 9010), -9 aluminium.

Type	EAN code	Thread	H mm	Ø mm	Colour	Strain relief	Suitable for adapter							PCS/ Package
							GA 69	GAT 69	GA 100	GAC 600	GA 300	XTSA 68	XTSA 67	
Fixed nipple	XTS 56/86-9	64100 14 522 56-8	M13 x1	8.6	9.0	Aluminium	XTSA 513	x	x	x	x	x	x	100/500
	XTS 58/8-9	64100 14 501 71-6	M10 x 1	8.0	7.4	Aluminium	XTSA 510	x	x	x	x	x	x	100/500
	GA 510-1	64100 14 500 34-4			7.0	Grey	Included	x	x	x	x	x	x	100/500
	GA 510-2	64100 14 520 86-1			7.0	Black	Included	x	x	x	x	x	x	100/500
	GA 510-3	64100 14 530 86-0			7.0	White	Included	x	x	x	x	x	x	100/500
	Rotating nipple *)													
XTSA 360/12-3	XTSA 360/8-1	64100 14 500 18-4	M10 x1	8.0	7.4	Grey	XTSA 510	x	x	x	x	x	x	100/500
	XTSA 360/8-2	64100 14 500 19-1	M10 x1	8.0	7.4	Black	XTSA 510	x	x	x	x	x	x	100/500
	XTSA 360/8-3	64100 14 500 20-7	M10 x1	8.0	7.4	White	XTSA 510	x	x	x	x	x	x	100/500
	XTSA 360/12-1	64100 14 522 82-7	M10 x1	12.0	7.4	Grey		x	x	x	x	x	x	100/500
	XTSA 360/12-2	64100 14 522 83-4	M10 x1	12.0	7.4	Black		x	x	x	x	x	x	100/500
	XTSA 360/12-3	64100 14 522 84-1	M10 x1	12.0	7.4	White		x	x	x	x	x	x	100/500
	XTSA 55/12-9	64100 14 501 55-6	M13 x 1	12.0	9.0	Aluminium		x	x	x	x	x	x	100/500
	XTSA 57/8-9	64100 14 501 59-4	M10 x 1	8.0	7.4	Aluminium	XTSA 510	x	x	x	x	x	x	100/500
	XTSA 57/8-9DD	64100 14 522 58-2	M10 x 1	8.0	6.9	Aluminium	XTSA 510	x	x	x	x	x	x	100/500
	XTSA 57/12-9	64100 14 501 57-0	M10 x 1	12.0	7.4	Aluminium		x	x	x	x	x	x	100/500
	XTSA 57/12-2	64100 14 520 92-2	M10 x 1	12.0	7.4	Black		x	x	x	x	x	x	100/500
	XTSA 57/17-9	64100 14 500 37-5	M10 x 1	17.0	7.4	Aluminium		x	x	x	x	x	x	100/500
XTSA 57/11/8-9	64100 14 500 38-2	M10 x 1	8.0	7.4	Aluminium	XTSA 510	x	x	x	x	x	x	100/500	
XTSA 57/12/8-9	64100 14 500 39-2	M10 x 1	8.0	7.4	Aluminium	XTSA 510	x	x	x	x	x	x	100/500	
XTSA 63-9	64100 14 522 59-9	M10 x 1			Aluminium		x	x	x	x	x	x	100/500	
Nipple joint *)	GA 37-1	64100 14 500 15-3		7.6	Grey		x	x	x	x	x	x	10/100	
	GA 37-2	64100 14 500 16-0		7.6	Black		x	x	x	x	x	x	10/100	
	GA 37-3	64100 14 500 17-7		7.6	White		x	x	x	x	x	x	10/100	
	GA 37M13-1	64100 14 500 27-6	M13 x 1	11	7.6	Grey	XTSA 513	x	x	x	x	x	10/100	
	GA 37M13-2	64100 14 500 28-3	M13 x 1	11	7.6	Black	XTSA 513	x	x	x	x	x	10/100	
	GA 37M13-3	64100 14 500 29-0	M13 x 1	11	7.6	White	XTSA 513	x	x	x	x	x	10/100	
Strain relief *)	XTSA 510-1	64100 14 500 32-0	M10 x 1	9.0	9.2	Grey							100/500	
	XTSA 510-2	64100 14 520 90-8	M10 x 1	9.0	9.2	Black							100/500	
	XTSA 510-3	64100 14 530 90-7	M10 x 1	9.0	9.2	White							100/500	
	XTSA 513-1	64100 14 500 33-7	M13 x 1	9.0	9.2	Grey							100/500	
	XTSA 513-2	64100 14 520 91-5	M13 x 1	9.0	9.2	Black							100/500	
	XTSA 513-3	64100 14 530 91-4	M13 x 1	9.0	9.2	White							100/500	
Thread	GAM 10-9	64100 14 501 75-4	M10 x 1										100/500	
	GAM 13-9	64100 14 501 76-1	M13 x 1										100/500	

*) Halogen free; VO-self-extinguishing.


Dimensions, look
at the table.



3-circuit adapter accessories

Available colours: – 1 grey (RAL 7040), – 2 black (RAL 9005), – 3 white (RAL 9010).

GA 70



FIX Point™ adapter connector

Type	EAN c ode	Colour	PCS/ Package
GA 70-1	64100 14 530 92-1	Grey	1/50
GA 70-2	64100 14 520 93-9	Black	1/50
GA 70-3	64100 14 530 93-8	White	1/50

- For GLOBAL 3-circuit adapters
- 10 A, 250 V, Safety class I
- Max. pull strength 50 N
- Max. torque 2.5 Nm
- For surface installation


GA 30



Type	EAN code	Colour	PCS/ Package
GA30-1	64100 14 500 12-2	Grey	1/50
GA30-2	64100 14 500 13-9	Black	1/50
GA30-3	64100 14 500 14-6	White	1/50

- For GA300 adapter
- 3 A, 250 V, Safety class I
- Max. pull strength 50 N
- Max. torque 2.5 Nm
- For surface installation


XTSA 71



Type	EAN code	Colour	PCS/ Package
XTSA 71-1	64100 14 530 97-6	Grey	1/25
XTSA 71-2	64100 14 520 96-0	Black	1/25
XTSA 71-3	64100 14 530 96-9	White	1/25

- For recessed installation with FIX Point™ GA 70
- Adjustable to different ceiling thicknesses, max. 30 mm
- For fixing hole diameters of Ø 105–125 mm

XTSK 17



Type	EAN code	Colour	PCS/ Package
XTSK 17-1	64100 14 520 17-5	Grey	10/100
XTSK 17-2	64100 14 520 17-5	Black	10/100
XTSK 17-3	64100 14 530 17-4	White	10/100

XTAO 16




XTAO 16-1	64100 14 500 49-8	Aluminium	5/50
-----------	-------------------	-----------	------

1-circuit adapters

Available colours: – 1 grey (RAL 7040), – 2 black (RAL 9005), – 3 white (RAL 9010).

GB 66 adapter




Type	EAN code	Colour	PCS/ Package
GB 66-1	64100 14 509 65-1	Grey	10/100
GB 66-2	64100 14 508 66-1	Black	10/100
GB 66-3	64100 14 509 66-8	White	10/100
GB 66L-1		Grey	100/9600
GB 66L-2		Black	100/9600
GB 66L-3		White	100/9600
GB 66CT	64100 14 522 51-3	Slot connection tool	1/50

- 6 A, 250 V, Safety class I
- Max. pull strength 50 N
- Max. torque 2.5 Nm
- To be used with stranded wire 0.5 ... 1 mm²

Slot connection. The conductors are pressed into the connectors by the connector lid or by the cable mounting tool.


GB 67 adapter

GB 67



Type	EAN code	Colour	PCS/ Package
GB 67-1	64100 14 509 73-6	Grey	10/100
GB 67-2	64100 14 508 67-8	Black	10/100
GB 67-3	64100 14 509 67-5	White	10/100


GB 67M



GB 67L-1		Grey	100/4800
GB 67L-2		Black	100/4800
GB 67L-3		White	100/4800

GB 67M-1		Grey	100
GB 67M-2		Black	100
GB 67M-3		White	100

GB 67S



GB 67S-2	64100 14 500 45-0	Schuko adapter	1/50
GB 67S-3	64100 14 509 68-2	Schuko adapter	1/50

*) Cable grip CG 69 included


- 16 A, 250 V, Safety class
- Max. pull strength 100 N
- Max. torque 2.5 Nm
- Connecting conductors max. 3 x 2.5 mm²

Screw-in connection. The conductors are connected with screws.

1-circuit adapters

Available colours: - 1 grey (RAL 7040), - 2 black (RAL 9005), - 3 white (RAL 9010).

GBB 67



Type	EAN code	Colour	PCS/ Package
GBB 67-1		Grey	20/960
GBB 67-2		Black	20/960
GBB 67-3		White	20/960


Adapter without trafo
Adapter without trafo
Adapter without trafo


- Max. pull strength 100 N
- Max. torque 2.5 Nm
- Connecting conductors max. 3 x 1.5 mm²
- Suits for use with dimmable fittings

- Max. pull strength 100 N
- Max. torque 2.5 Nm
- Connecting conductors max. 3 x 1.5 mm²
- Suits for use with dimmable fittings

Nipples for 1-circuit adapters

Available colours: -1 grey (RAL 7040), -2 black (RAL 9005), -3 white (RAL 9010), -9 aluminium.

Suitable for adapter										
Type	EAN code	Thread	H mm	Ø mm	Colour	Strain relief	GB 66	GB 67	GBB 67	PCS/ Package
	Fixed nipple XTS 56/86-9	64100 14 522 56-8	M13 x 1	8.6	9.0	Aluminium	XTSA 513	x	x	100/500
	XTS 58/8-9	64100 14 501 71-6	M10 x 1	8.0	7.4	Aluminium	XTSA 510	x	x	100/500
	GA 510-1	64100 14 500 34-4								
	GA 510-2	64100 14 520 86-1								
	GA 510-3	64100 14 530 86-0								
	GB 510-1	64100 14 500 35-1								
	GB 510-2	64100 14 508 58-6								
	GB 510-3	64100 14 509 58-3								
	Rotating nipple *) XTSA 360/8-1	64100 14 500 18-4	M10 x 1	8.0	7.4	Grey	XTSA 510	x	x	100/500
	XTSA 360/8-2	64100 14 500 19-1	M10 x 1	8.0	7.4	Black	XTSA 510	x	x	100/500
	XTSA 360/8-3	64100 14 500 20-7	M10 x 1	8.0	7.4	White	XTSA 510	x	x	100/500
	XTSA 360/12-1	64100 14 522 82-7	M10 x 1	12.0	7.4	Grey		x	x	100/500
	XTSA 360/12-2	64100 14 522 83-4	M10 x 1	12.0	7.4	Black		x	x	100/500
	XTSA 360/12-3	64100 14 522 84-1	M10 x 1	12.0	7.4	White		x	x	100/500
	XTSA 55/12-9	64100 14 501 55-6	M13 x 1	12.0	9.0	Aluminium		x	x	100/500
	XTSA 57/8-9	64100 14 501 59-4	M10 x 1	8.0	7.4	Aluminium	XTSA 510	x	x	100/500
	Nipple joint *) GA 37-1	64100 14 500 15-3								
	GA 37-2	64100 14 500 16-0								
	GA 37-3	64100 14 500 17-7								
	GA 37M13-1	64100 14 500 27-6								
	GA 37M13-2	64100 14 500 28-3								
	GA 37M13-3	64100 14 500 29-0								
	XTSA 63-9	64100 14 522 59-9	M10 x 1			Aluminium		x	x	100/500
	GA 57/10-1	64100 14 509 56-9	M10 x 1	10.0	7.0	Grey	XTSA 510	x	x	100/500
	Strain relief *) XTSA 510-1	64100 14 500 32-0	M10 x 1	9.0	9.2	Grey		x	x	10/100
	XTSA 510-2	64100 14 520 90-8	M10 x 1	9.0	9.2	Black		x	x	10/100
	XTSA 510-3	64100 14 530 90-7	M10 x 1	9.0	9.2	White		x	x	10/100
	XTSA 513-1	64100 14 500 33-7	M13 x 1	9.0	9.2	Grey	XTSA 513	x	x	10/100
	XTSA 513-2	64100 14 520 91-5	M13 x 1	9.0	9.2	Black	XTSA 513	x	x	10/100
	XTSA 513-3	64100 14 530 91-4	M13 x 1	9.0	9.2	White	XTSA 513	x	x	10/100
	Thread GAM 10-9	64100 14 501 75-4	M10 x 1							
	GAM 13-9	64100 14 501 76-1	M13 x 1							



Dimensions, look at the table.

*¹) Halogen free, V0-self-extinguishing.