

96638000 TONIC XS 1700-930 3GU FL WH




Tonic

LED spotlight for 3 phase track installations with flood light distribution and stabilized color temperature. Electronic, fixed output control gear. Class II electrical, IP20. Body: Die-cast aluminium white micro-textured paint. Reflector: PC sputtered. Spotlight rotatable through 360° and pivotable through 90°. Complete with 3000K LED


Dimensions: Ø55 x 125 mm
 Luminaire input power: 14.5 W
 Luminaire luminous flux: 1544 lm
 Luminaire efficacy: 107 lm/W
 Weight: 0.4 kg



TLG_TNC2_F_XS_WH.jpg



TLG_TNC2_M_XS.wmf



96638000_TONIC_XS_1700_930_3GU_FL_WH.ltd

Lamp position: STD - standard
 Light Source: LED
 Luminaire luminous flux*: 1544 lm
 Luminaire efficacy*: 107 lm/W
 Colour Rendering Index min.: 90
 Correlated colour temperature*: 3000 Kelvin
 LOR: 1,00 ULOR: 0,00 DLOR: 1,00

Chromaticity tolerance (initial MacAdam): 3
 Rated median useful life*:
 L80 50000 h at 25 °C
 Ballast: 1x HF_
 Luminaire input power*: 14.5 W Power factor = 0.9
 Dimming: Fixed output
 Maintenance category CIE 97: D - Enclosed IP2X