


LED pendant luminaire

Linear, energy-efficient TECTON MIREL LED continuous row luminaire made of roll-formed sheet steel in polyester lacquer finish, black. Luminaire input power: 19.9 W, Slave luminaire for DALI control (DALI only) with LED converter. LED service life lasts 100000 h before luminous flux is reduced to 90% of the initial value. Chromaticity tolerance (initial MacAdam): 3. Luminaire efficacy: 127 lm/W. Luminaire luminous flux: 2520 lm. Colour rendering Ra > 80, colour temperature 4000 K. LED continuous row luminaire with 4 highly efficient mid-power LEDs per lens segment. Light is guided via the reflector- the lens combination creates a unique continuous row design with photometric benefits such as very low UGR values with minimum light emission surface. Lens reflector enables UGR <19 and luminance of <3000 cd/m². All-in-one solution: Batten luminaire, lamp and reflector are combined in a single product. Base support of LED continuous-row luminaire of sheet steel in polyester lacquer finish, black. 100% flexible, tool-free mechanical and electrical installation using CLIX-technology by means of two side-mounted rotary levers on the TECTON trunking. No ultraviolet or infrared radiation. Impact strength: IK03. ambient temperature: -20°C to +30°C. Luminaire wired with halogen-free leads. Dimensions: 1000 x 60 x 85 mm weight: 1.5 kg




ZS_TEC_F_LED_mirel_Balken_BK.jpg



ZS_TEC_M_C_MEL_LED_Balken.wmf

Light Distribution

STD - standard



D42326AA_TECTON_MIREL_LED2700-840_L1000_LDO_BK.Idt

- Light Source: LED
- Luminaire luminous flux*: 2520 lm
- Luminaire efficacy*: 127 lm/W
- Colour Rendering Index min.: 80
- Ballast: 1 x 28000655 LCA 50W 100-400mA one4all Ip PRE
- Correlated colour temperature*: 4000 Kelvin
- Chromaticity tolerance (initial MacAdam): 3
- Rated median useful life*: L90 100000 h at 25 °C
- Luminaire input power*: 19.9 W Power factor = 0.91
- Standby Power*: 0.15 W
- Dimming: LDO dimmable to 1% over DALI
- Maintenance category CIE 97: D - Enclosed IP2X
- Total harmonic distortion (THD): 16.20 %

This product contains a light source of energy efficiency class D.

All values marked with an * are rated values. Connected electrical load and luminous flux are subject to an initial tolerance of +/- 10%, the most similar colour temperature is subject to an initial tolerance of +/- 150K. Unless stated otherwise, the values apply to an ambient temperature of 25°C.